

Shaker



Main features

- Soft start, Soft stop function
- auto-Repeated forward and reverse rotation
- Time adjusting function (mm:ss, hh:mm, continuous)
- Free to adjust RPM during the operation
- Free Voltage applied
- Long lasting Brushless DC Motor
- Can be installed with various accessories

WS-350S / WS-500S

	WS-350S	WS-500S
Dimension	350 x 420 x 97(H)mm	500 x 520 x 100(H)mm
Platform Capacity (Flask)		
100 _{ml}	16	49
250 _{ml}	13	25
500 _{ml}	9	16
1000 _{ml}	4	9
2000 _{ml}	2	5
Platform Size	350 x 350(mm)	480 x 480(mm)
Controller	Microprocessor Control	Microprocessor Control
Speed		
Range	30~350 (rpm)	30~350 (rpm)
Increment	10 rpm	10 rpm
Time		
Range Selectable	99mm,59s, 99h,59m, continuous	99mm,59s, 99h,59m, continuous
Motor	Brushless DC Motor	Brushless DC Motor
Motor Driving Direction	Forward, Reverse, Auto Reverse	Forward, Reverse, Auto Reverse
Stroke	22mm	22mm
Display	7-Segment LED Display	7-Segment LED Display
Operating Inqut	Touch Button	Touch Button
Weight	18 kg	31kg
Power	AC96~254V, 50/60Hz Free-voltage	AC96~254V, 50/60Hz Free-voltage